

SWING CHECK VALVE WITH SIDE MOUNTED 2-STAGE OIL CUSHION

SERIES NO. 7900S2

STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
30	WEIGHT LEVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
31	WEIGHT	DUCTILE IRON ASTM A536, GRADE 65-45-12
32	KEY	STEEL
33	BOLT	PLATED STEEL
34	BOLT	PLATED STEEL
35	NUT	PLATED STEEL
36	WASHER	PLATED STEEL
40	CYLINDER BRACKET	STEEL
42	OIL CYLINDER	STEEL
43	CYLINDER PIN	PLATED STEEL
44	CLEVIS PIN	PLATED STEEL
45	CYLINDER LEVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
46	BOLT	PLATED STEEL
47	WASHER	PLATED STEEL
53	BREATHER/FILTER	STEEL, ZINC PLATED
60	OIL ACCUMULATOR	STAINLESS STEEL T304
62	OIL FILL PORT	BRASS
63	FLOW CONTROL VAVLE	BRASS

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

Revised 8-28-14 (Rev 1)

MATERIALS OF CONSTRUCTION

DATE 2/26/13

VAL-MATIC®

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-7920S2-M