

PART NO.	PART NAME	MATERIAL
1	BODY	CAST IRON ASTM A126, CLASS B
2	COVER	CAST IRON ASTM A126, CLASS B
3	DISC	BUNA-N 35 DUROMETER W/ ALUMINUM AND NYLON FABRIC REINFORCEMENT (TOTALLY ENCAPSULATED)
4	GASKET	COMPRESSED NON-ASBESTOS FIBER
5	COVER BOLT	ALLOY STEEL

ANSI CLASS 125											
VALVE SIZE	MODEL NO.	Α	В	С	D	Е	F	BOLT SIZE	NO. OF BOLTS		
8	508DG	19 <sup>1</sup> / <sub>2</sub>	11 3/4	13 <sup>1</sup> / <sub>2</sub>	1 <sup>1</sup> / <sub>8</sub>	8	7 <sup>5</sup> /8	3/4	8		
10	510DG	24 1/2	14 <sup>1</sup> / <sub>4</sub>	16	1 <sup>3</sup> / <sub>16</sub>	10	9 7 <sub>/8</sub>	7/8	12		
12	512DG	27 1/2	17	19	1 1/4	12	11 <sup>3</sup> / <sub>8</sub>	7/8	12		

VALVE OPENING PRESSURE SYSTEM OPERATING PRESSURE TEMPERATURE 1" WATER COLUMN 15" WATER COLUMN 150° F.

Revised 3-6-98

DRWG. NO.

SWING-FLEX® CHECK VALVE FOR DIGESTER GAS SERVICE

DATE 11-20-97



VALVE AND MANUFACTURING CORP.

SS-1432