ABOVE GROUND WORM GEAR ACTUATOR

3P24 through 3R24

PART NO.	PART NAME	MATERIAL
1	HOUSING	DUCTILE IRON ASTM A536, GRADE 80-35-06
2	WORM GEAR	BRONZE
3	WORM	HARDENED STEEL
4	COVER	DUCTILE IRON ASTM A536, GRADE 80-55-06
5	SHAFT ADAPTER	CAST IRON ASTM A126, CLASS B
6	O-RING SEAL	BUNA-N
7	ROLLER THRUST BEARING	CARBON STEEL, GRADE 1045
10	GASKET	COMPRESSED NON-ASBESTOS FIBER
11	HANDWHEEL	STEEL
12	OPERATING NUT (OPTIONAL)	CAST IRON ASTM A126, CLASS B
13	CHAINWHEEL (OPTIONAL)	DUCTILE IRON
14	COVER BOLT	CARBON STEEL
15	INDICATOR BOLT	CARBON STEEL
17	INDICATOR	CAST IRON ASTM A126, CLASS B
18	SPRING PIN	STAINLESS STEEL
19	STOP ADJUSTMENT SCREW	CARBON STEEL
20	STOP COVER BOLT	CARBON STEEL
21	JAM SCREW	CARBON STEEL
22	END CAP	CAST IRON ASTM A126, CLASS B
23	END CAP GASKET	COMPRESSED NON-ASBESTOS FIBER
24	MOUNTING BOLT	CARBON STEEL
30	SPUR GEAR ASSEMBLY	CAST IRON AND ALLOY STEEL

NOTE: ALL SPECIFICATIONS AS LAST REVISED.

Revised 8-10-01

MATERIALS OF CONSTRUCTION

DATE 8/15/00

DRWG. NO.

VM-3P24-M