BURIED SERVICE WORM GEAR ACTUATOR

8A02 through 8D02

PAF	RT NO.	PART NAME	MATERIAL
	1	HOUSING	CAST IRON ASTM A126, CLASS B
	2	WORM GEAR	DUCTILE IRON ASTM A536, GRADE 65-45-12
	3	WORM	CARBON STEEL ASTM A108, GRADE 1045
	4	COVER	CAST IRON ASTM A126, CLASS B
	6	O-RING	BUNA-N 70 DUROMETER
	7	ROLLER THRUST BEARING	CARBON STEEL GRADE 1045
	8	SHAFT BEARING	PERMANENTLY LUBRICATED BRONZE
	9	SHAFT	STAINLESS STEEL
	10	GASKET	COMPRESSED NON-ASBESTOS FIBER
	12	OPERATING NUT	CAST IRON ASTM A126, CLASS B
	14	COVER BOLT	CARBON STEEL
	18	WORM SPRING PIN	CARBON STEEL
	19	SPRING PIN	CARBON STEEL
	20	STOP ADJUSTMENT SCREW	CARBON STEEL
	21	JAM NUT	STEEL-ZINC PLATED
	23	OIL SEAL	STEEL & RUBBER
	24	MOUNTING BOLT	CARBON STEEL (NOT SHOWN)
	25	KEY	ALLOY STEEL
	26	WORM GEAR BEARING	PERMANENTLY LUBRICATED BRONZE

NOTE: ALL SPECIFICATIONS AS LAST REVISED.

Revised 4-15-99

DRWG. NO.

MATERIALS OF CONSTRUCTION DATE 4/11/96

