



COLD WORKING PRESSURE 150 PSI (150B) 250 PSI (250B)

FLANGE DIMENSIONS, INCHES

VALVE SIZE	AWWA C504 CLASS	A	B	C	D	E Qty.	E Tap	E Deep	F	G	H	J	K	L	N	P	T	TURNS TO OPEN	NO. OF BOLTS	BOLT SIZE	ACTUATOR SIZE	SHPG WT. lb.
30	150B	12.00	36.00	38.75	2.12	4	1 1/4-7	2.00	27.38	29.12	8.50	34.50	31.00	24.00	6.00	14.25	8.88	63	28	1.25	LS-5	2435
	250B	13.75	39.25	43.00	3.00		1 3/4-5	3.00							6.88	8.00	1.75			2800		
36	150B	12.00	42.75	46.00	2.38	4	1 1/2-6	2.38	29.50	31.88	8.50	37.25	31.00	24.00	6.00	14.25	11.88	63	32	1.50	LS-5	3425
	250B	14.00	46.00	50.00	3.38		2-4 1/2	3.38							7.00	10.88	2.00			4000		

Revised 8-5-05

150B & 250B FLANGED BUTTERFLY VALVE WITH HANDWHEEL ACTUATOR AND POSITION INDICATOR

DATE 5-28-99

VAL-MATIC® VALVE AND MANUFACTURING CORP.

DRWG. NO.
VM-2030/LSA