



SEE DRAWING NO. VM-2030-M FOR STANDARD 250B MATERIALS OF CONSTRUCTION.

COLD WORKING PRESSURE 250 PSI (250B)

**CLASS 125 LB. DUCTILE IRON FLANGE DIMENSIONS, INCHES**

VALVE SIZE	AWWA C504 CLASS	A	B	C	D	E Qty.	E Tap	E Deep	F	G	H	J	K	L	N	P	T	TURNS TO OPEN	NO. OF BOLTS	BOLT SIZE	ACTUATOR SIZE	SHPG WT. lb.
30	250B	12.00	36.00	38.75	2.12	4	1 1/4-7	2.00	27.38	29.12	8.50	34.50	31.00	24.00	6.00	14.25	8.88	63	28	1 1/4	LS-5	2435
36	250B	12.00	42.75	46.00	2.38	4	1 1/2-6	2.38	29.50	31.88	8.50	37.25	31.00	24.00	6.00	14.25	11.88	63	32	1 1/2	LS-5	3425

Revised 8-23-05

250B / 125 LB. DUCTILE IRON FLANGED BUTTERFLY VALVE WITH HANDWHEEL ACTUATOR AND POSITION INDICATOR

DATE 9-7-00

**VAL-MATIC®** VALVE AND MANUFACTURING CORP.

DRWG. NO. VM-2430/LSA