

DUAL DISC[®] CHECK VALVE

14"-30" STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY	CAST IRON ASTM A126, CLASS B W/ BUNA-N RESILENT SEAT MOLDED TO BODY
2	DISC	ALUMINUM BRONZE ASTM B148, ALLOY 95200
3	TORSION SPRING	STAINLESS STEEL T316, ASTM A313 (14"-16") STAINLESS STEEL 17-7PH, ASTM A313 (18"-30")
4	HINGE PIN	STAINLESS STEEL T316, ASTM A276
5	STOP PIN	STAINLESS STEEL T316, ASTM A276
6	THRUST BEARING	STAINLESS STEEL T316, ASTM A240
7	HINGE PIN RETAINER	STEEL
8	STOP PIN RETAINER	STEEL
9	STABILIZATION SPHERE	BUNA-N

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

Revised 1-27-03

MATERIALS OF CONSTRUCTION

DATE 6/21/93

VAL-MATIC[®]

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-8814-M