

AIR/VACUUM VALVE

1/2" to 3" SERIES NO. 100SSV

STANDARD MATERIALS OF CONSTRUCTION

| <u>PART NO.</u> | <u>PART NAME</u> | <u>MATERIAL</u> |
|-----------------|------------------|---|
| 1 | BODY | CAST IRON ASTM A126, CLASS B (INTERIOR / EXTERIOR FUSION BONDED EPOXY) |
| 2 | COVER | CAST IRON ASTM A126, CLASS B (INTERIOR / EXTERIOR FUSION BONDED EPOXY) |
| 3 | BAFFLE | DUCTILE IRON ASTM A536, GRADE 65-45-12 (INTERIOR / EXTERIOR FUSION BONDED EPOXY) |
| 4 | SEAT | EPDM |
| 5 | FLOAT | STAINLESS STEEL T316, ASTM A240 |
| 6 | GASKET | COMPRESSED NON-ASBESTOS FIBER |
| 7 | COVER BOLT | STAINLESS STEEL T316, ASTM F593 |
| 8 | RETAINING SCREW | STAINLESS STEEL T316, ASTM F593 |
| 9 | GUIDE BUSHING | STAINLESS STEEL T316, ASTM A240 |
| 14 | PIPE PLUG | STAINLESS STEEL |
| 20 | GUIDE SHAFT | STAINLESS STEEL T316, ASTM A240 |

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

MATERIALS OF CONSTRUCTION

DATE 2/3/10

VAL-MATIC[®] VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-100SSV-M