



SEE DRAWING NUMBER VM-9612T-M FOR ANSI CLASS 150 MATERIALS OF CONSTRUCTION.

ANSI CLASS 150												
VALVE SIZE	MODEL NO.	A	B	C	D	E	F	G	H	J	BOLT SIZE	NO. OF BOLTS
12	9612T	24.00	17.00	19.00	1.25	12.00	26.00	21.00	34.00	21.00	7/8	12
14	9614T	30.00	18.75	21.00	1.38	14.00	29.00	25.00	36.00	21.00	1	12
16	9616T	30.00	21.25	23.50	1.44	16.00	32.00	28.00	43.00	24.00	1	16
18	9618T	33.00	22.75	25.00	1.56	18.00	36.00	30.00	45.00	24.00	1 1/8	16
20	9620T	32.00	25.00	27.50	1.69	20.00	39.00	32.00	53.00	28.00	1 1/8	20
24	9624T	38.00	29.50	32.00	1.88	24.00	46.00	37.00	56.00	28.00	1 1/4	20
30	9630T	52.00	36.00	38.75	2.13	30.00	55.00	47.00	66.00	36.00	1 1/4	28
36	9636T	59.50	42.75	46.00	2.38	36.00	65.00	51.00	78.00	36.00	1 1/2	32
42	9642T	62.50	49.50	53.00	2.63	42.00	73.00	59.00	89.00	43.00	1 1/2	36
48	9648T	65.00	56.00	59.50	2.75	48.00	82.00	69.00	99.00	43.00	1 1/2	44
54	9654T	78.00	62.75	66.25	3.00	54.00	90.88	75.00	122.50	48.00	1 3/4	44
60	9660T	87.00	69.25	73.00	3.13	60.00	99.00	83.50	120.00	60.00	1 3/4	52
66	9666T	96.00	76.00	80.00	3.25	66.00	108.00	92.00	132.00	60.00	1 3/4	52

NOTE:  
FOR VERTICAL FLOW UP INSTALLATION, CONSULT FACTORY.

Revised 8-4-16

ANSI CLASS 150 TILTED DISC<sup>®</sup> CHECK VALVE W/ TOP MOUNTED OIL DASHPOT

DATE 1-6-94

**VAL-MATIC<sup>®</sup>** VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-9612T