



SEE DRAWING NO. VM-9806B-M FOR ANSI CLASS 125 MATERIALS OF CONSTRUCTION.

ANSI CLASS 125														
VALVE SIZE	MODEL NO.	A	B	C	D	E	F	G	H	J	K	L		
		BOLT SIZE		NO. OF BOLTS										
6	9806B	15.00	9.50	11.00	1.00	6.00	16.00	6.50	3/4	8	9.00	16.00	12.00	3.00
8	9808B	19.50	11.75	13.50	1.13	8.00	19.00	8.00	3/4	8	8.00	17.00	11.00	4.00
10	9810B	24.50	14.25	16.00	1.19	10.00	23.00	9.50	7/8	12	5.00	18.00	9.00	5.00

SEE DRAWING NO. VM-9706B-M FOR ANSI CLASS 250 MATERIALS OF CONSTRUCTION.

ANSI CLASS 250														
VALVE SIZE	MODEL NO.	A	B	C	D	E	F	G	H	J	K	L		
		BOLT SIZE		NO. OF BOLTS										
6	9706B	15.00	10.63	12.50	1.44	6.00	16.00	6.50	3/4	12	9.00	16.00	12.00	3.00
8	9708B	19.50	13.00	15.00	1.63	8.00	19.00	8.00	7/8	12	8.00	17.00	11.00	4.00
10	9710B	24.50	15.25	17.50	1.88	10.00	23.00	9.50	1	16	5.00	18.00	9.00	5.00

**NOTES:**

DIMENSIONS "K" AND "L" REPRESENT THE MINIMUM CLEARANCE REQUIRED TO REMOVE DASHPOT UNIT. HOWEVER DIMENSION "L" CAN BE REDUCED TO 1" IF SPACE REQUIREMENTS DICTATE. FOR VERTICAL FLOW UP INSTALLATION, CONSULT FACTORY.

PIVOT PIN COVER DETAIL  
VALVE SIZE 6"

Revised 8-4-16

ANSI CLASS 125 and 250 TILTED DISC® CHECK VALVE WITH BOTTOM MOUNTED OIL DASHPOT

DATE 8-12-80

DRWG. NO.

VM-9806B

**VALMATIC®**  
VALVE AND MANUFACTURING CORP.