



SEE DRAWING NO. VM-22-M FOR STANDARD MATERIAL OF CONSTRUCTION.

VALVE SIZE	MODEL NO. **	INLET SIZE	OUTLET SIZE	MAX. W.P. P.S.I.	ORIFICE SIZE
1/2" - 3/4" *	22.4	3/4" N.P.T.	1/2" N.P.T.	175	3/32"
1"	22.3	1" N.P.T.	1/2" N.P.T.	175	3/32"
1/2"	22.7	1/2" N.P.T.	1/2" N.P.T.	300	1/16"
1/2" - 3/4" - 1" *	22.9	1" N.P.T.	1/2" N.P.T.	300	1/16"

* When multiple size inlets are indicated for a specific model number, the valve is threaded for the largest size indicated and a reducer bushing is provided for the smaller sizes.

** Add "H" to Model No. for optional screened hood SPK-5H.

1	BODY	11	ORIFICE BUTTON
2	COVER	12	PIVOT PIN
3	LEVER FRAME	13	PIN RETAINER (NOT SHOWN)
4	SEAT	14	PIPE PLUG
5	FLOAT	17	FLOAT RETAINER
6	GASKET	21	LOCATOR
7	COVER BOLT	23	SCREENED HOOD
10	FLOAT ARM	34	LOCK WASHER

Revised 4-13-04

AIR RELEASE VALVE

DATE 5-8-69

VAL-MATIC[®]

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-22