

SWING-FLEX[®] CHECK VALVE
SERIES NO. 500A ANSI CLASS 125
STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY (2" - 24")	DUCTILE IRON ASTM A536, GRADE 65-45-12
1	BODY (30" - 42")	CAST IRON ASTM A126, CLASS B
2	COVER (2" - 24")	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER (30" - 42")	CAST IRON ASTM A126, CLASS B
3	DISC	BUNA-N W/ ALLOY STEEL & NYLON REINFORCEMENT
4	COVER SEAL	BUNA-N OR COMPRESSED NON-ASBESTOS FIBER
5A	COVER BOLT	ALLOY STEEL SAE GRADE 5, PLATED
5B	COVER BOLT NUT (4"-12")	ALLOY STEEL, PLATED
5C	WASHER	ALLOY STEEL, PLATED

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

Revised 10-17-07

MATERIALS OF CONSTRUCTION

DATE 4/24/03



VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-502A-M