



SEE DRAWING NO. VM-9806B-M FOR ANSI CLASS 125 MATERIALS OF CONSTRUCTION.

ANSI CLASS 125														
VALVE SIZE	MODEL NO.	A	B	C	D	E	F	G	BOLT SIZE	NO. OF BOLTS	H	J	K	L
6	9806B	15	9 1/2	11	1	6	16	6 1/2	3/4	8	9	16	12	3
8	9808B	19 1/2	11 3/4	13 1/2	1 1/8	8	19	8	3/4	8	8	17	11	4
10	9810B	24 1/2	14 1/4	16	1 3/16	10	23	9 1/2	7/8	12	5	18	9	5

SEE DRAWING NO. VM-9706B-M FOR ANSI CLASS 250 MATERIALS OF CONSTRUCTION.

ANSI CLASS 250														
VALVE SIZE	MODEL NO.	A	B	C	D	E	F	G	BOLT SIZE	NO. OF BOLTS	H	J	K	L
6	9706B	15	10 5/8	12 1/2	1 7/16	6	16	6 1/2	3/4	12	9	16	12	3
8	9708B	19 1/2	13	15	1 5/8	8	19	8	7/8	12	8	17	11	4
10	9710B	24 1/2	15 1/4	17 1/2	1 7/8	10	23	9 1/2	1	16	5	18	9	5

**NOTE**  
DIMENSIONS "K" AND "L" REPRESENT THE MINIMUM CLEARANCE REQUIRED TO REMOVE DASHPOT UNIT. HOWEVER DIMENSION "L" CAN BE REDUCED TO 1" IF SPACE REQUIREMENTS DICTATE.

Revised 7-10-02

ANSI CLASS 125 and 250 TILTED DISC® CHECK VALVE WITH BOTTOM MOUNTED OIL DASHPOT

DATE 8-12-80



VALVE AND MANUFACTURING CORP.

DRWG. NO. VM-9806B