

AIR/VACUUM VALVE

4" - 20" SERIES NO. 100S

MATERIALS OF CONSTRUCTION

PART NO.	PART NAME	STANDARD MATERIAL	OPTIONAL MATERIAL
1	BODY	CAST IRON ASTM A126, CLASS B	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER	CAST IRON ASTM A126, CLASS B	DUCTILE IRON ASTM A536, GRADE 65-45-12
4	SEAT	BUNA-N	EPDM, FKM
5	FLOAT	STAINLESS STEEL T316, ASTM A240	-
6	GASKET	COMPRESSED NON-ASBESTOS FIBER	
7	COVER BOLT	ALLOY STEEL SAE, GRADE 5, ZINC PLATED	STAINLESS STEEL, T316
8	RETAINING SCREW	STAINLESS STEEL T316, ASTM F593	
9	GUIDE BUSHING	STAINLESS STEEL T316, ASTM A240	-
15	CUSHION	BUNA-N	-
23	SCREENED HOOD (4") SCREENED HOOD (6"-20") (OPTIONAL)	GALVANIZED IRON STEEL - #1020	-
27	INTERNAL WASHER (8"-20")	STAINLESS STEEL T316, ASTM A240	-
28	PIPE PLUG	STEEL	STAINLESS STEEL, T316

Revised: 1/3/23

MATERIALS OF CONSTRUCTION

DATE: 10/3/03

VALMATIC[®]

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-104S-M