

COLD WORKING PRESSURE 150 PSI (150B) 250 PSI (250B)

DRAWING DEPICTS 42" CLASS 150B SIZE TO SCALE

DIMENSIONS, INCHES																							
VALVE SIZE	AWWA C504 CLASS		В	С	D	E Qty.	E Tap	E Deep	F	G	Н	J	K1	K2	L	Ρ	Т	TURNS TO OPEN	NO. OF BOLTS	BOLT SIZE	ACTU- ATOR SIZE	SHPG. WT. LBS.	
42				53.00 57.00		4	11/2-6 2-41/2	2.50 3.12	35.25	35.88	8.50	41.75	19.50	17.50	11.75	17.75	14.81 13.69	178	36	1 1/2 2	LS-5.2A	4559 5489	
48				59.50 65.00		4	11/2–6 2–41/2		39.31	41.44	10.50	50.18	24.88	22.25	17.50	21.88	16.38 15.00	276	44 40	1 1/2 2	LS-6A	6950 8510	
54	150B	15.00	62.75	66.25	3.00	8	13/4–5	2.62	44.25	45.44	10.50	54.18	24.88	22.25	17.50	21.88	19.25	276	44	1 3/4	LS-6A	9280	
60	150B	15.00	69.25	73.00	3.12	8	13/4–5	2.62	48.25	51.88	10.50	61.88	24.88	22.25	17.50	21.88	22.25	276	52	1 3/4	LS-6A	12900	
66	150B	18.00	76.00	80.00	3.38	8	13/4–5	2.62	53.31	58.12	10.50	68.12	24.88	22.25	17.50	21.88	23.75	276	52	1 3/4	LS-6A	14840	
72	150B	18.00	82.50	86.50	3.50	8	13/4–5	2.38	59.00	61.00	14.00	72.00	32.25	27.75	22.00	28.75	26.75	547	60	1 3/4	LS-7A	17840	
78	150B	18.00	89.00	93.00	2.75	8	2-41/2	2.50	54.50	73.63	14.00	84.63	32.25	27.75	22.00	28.75	29.13	547	64	2	LS-7.3A	14040	
84A	150B	19.00	95.50	99.75	2.88	8	2-41/2	2.88	58.75	76.25	14.00	87.25	32.25	27.75	22.00	28.75	31.69	547	64	2	LS-7.2A	16440	
90	150B	20.00	102.00	106.50	3.00	8	21/4-41/2	3.00	62.88	82.50	14.00	93.50	32.25	27.75	22.00	28.75	34.19	547	68	2 1/4	LS-7A	19740	
Rev 10-23-19														23-19									
	15	0B &	250B	FLAN	IGED	BU	TTERF	LY V	ALVE	WITH	HBUF	RIED	SER	ICE A	ACTU.	ATOF	<u>۲</u>		DATE 3-11-11				
							®												DRWG. NO.				
	·	V	\L	M	AT	IC		ALVE	E AN	ID M	IANU	FAC	TURI	NG (CORF) .				VM-2042/BLS			