

SWING-FLEX® CHECK VALVE

SERIES NO. 500A ANSI CLASS 125

OPTIONAL MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
3	DISC	BUNA-N W/ ALLOY STEEL & NYLON REINFORCEMENT
4	COVER O-RING (2"-48")	BUNA-N 70 DURO
5A	COVER BOLT	ALLOY STEEL SAE J429 GRADE 5, PLATED
5B	COVER BOLT NUT (4"-12")	ALLOY STEEL SAE J429 GRADE 5, PLATED
5C	WASHER	ALLOY STEEL, PLATED
6A	COVER PIPE PLUG	STEEL
6B	BODY PIPE PLUG (2"-6")	STEEL
	BODY PIPE PLUG (8"-48")	STEEL, NICKEL PLATED

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

Revised 8-19-20

MATERIALS OF CONSTRUCTION

DATE 4/24/03

VALMATIC®

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-502A-M