

**SWING-FLEX<sup>®</sup> CHECK VALVE**  
**SERIES NO. 500AMI ANSI CLASS 125**  
STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
3	DISC	BUNA-N W/ ALLOY STEEL & NYLON REINFORCEMENT
4	COVER SEAL (4"-48") COVER SEAL (2"-3")	BUNA-N ASTM D2000 COMPRESSED NON-ASBESTOS FIBER
5A	COVER BOLT	ALLOY STEEL SAE J429 GRADE 5, PLATED
5B	COVER BOLT NUT (4"-12")	ALLOY STEEL SAE J429 GRADE 5, PLATED
5C	WASHER	ALLOY STEEL, PLATED
6B	BODY PIPE PLUG (2"-6") BODY PIPE PLUG (8"-48")	STEEL STEEL, NICKEL PLATED
14	MECHANICAL INDICATOR (OPTIONAL, SIZES 3"-48")	ALUMINUM BRONZE, 17-4 STAINLESS STEEL

NOTE: ALL SPECIFICATIONS AS  
LAST REVISED.

Revised 11-8-19

**MATERIALS OF CONSTRUCTION**

DATE 8/13/08

**VAL-MATIC<sup>®</sup>**

**VALVE AND MANUFACTURING CORP.**

DRWG. NO.

**VM-503AMI-M**