	B COLD WORKING PRESSURE - CWP B B B COLD WORKING PRESSURE - CWP B B COLD WORKING PRESSURE - CWP B COLD WORKING PRESSURE - CWP B C C C C C C C C C C C C C																	
	H - 6 NOTE: DIMENSIONS "L" AND "M" REPRESENT THE MINIMUM CLEARANCE REQUIRED TO REMOVE OR INSTALL BACKFLOW ACTUATOR. * DIMENSION "H" DOES NOT EXTEND PAST FLANGE ON VALVE SIZES 2" THRU 3", 30" THRU 48". 2" & 2 ½" DO NOT HAVE MECHANICAL INDICATOR BOSS.																	
	DRAWING DEPICTS 24" SIZE TO SCALE SEE DRAWING NO. VM-504XD-M FOR STANDARD MATERIALS OF CONSTRUCTION ANSI CLASS 125																	
VALVE SIZE	MODEL NO.	CWP (PSI)	A	В	С	D	E	F	G	*H	J	К	L	M	BOLT SIZE	NO. OF BOLTS	NO. BOLTS	SHPG. WT.
2	502BFXD	200	8.00			0.69	2.00	· ·	1.63		6.75		1.50	1.50	5/8	4		27
2 1/2	525BFXD	200	8.50			0.75		N/A	1.63		7.00		1.50	1.50	5/8	4		32
3	503BFMIXD	200	9.50	6.00		0.81	3.00		1.63		7.50		1.50	1.50	5/8	4		45
4	504BFMIXD 506BFMIXD	200 200	11.50		9.00 11.00	0.93		10.63 11.69			10.75	8.25	2.50 3.00	2.50	5/8 3/4	8		70 130
8	508BFMIXD	200			13.50			13.25				16.00		5.75	3/4	8		250
10	510BFMIXD		24.50					15.63				21.00		5.75	7/8	12		430
10	512BFMIXD		27.50					17.19				24.00		6.50	7/8	12		660
14	514BFMIXD	200						17.81				23.25		6.50	1	12		750
16	516BFMIXD	200	32.00					19.06				25.25		6.50	1	16		900
18	518BFMIXD				25.00			20.25	3.13	3.25	33.75	28.25	6.50	6.50	1 1/8	16		1230
20	520BFMIXD							21.69		5.88	37.50	30.63	8.00	8.00	1 1/8	20	. — —	1750
24	524BFMIXD							24.50				36.00		8.00	1 1/4	20		2400
30	530BFMIXD							27.81						8.00	1 1/4	28		4350
36	536BFMIXD	200	63.00	42.75	46.00	2.38	36.00	32.63	3.88	-0.38	49.00	55.00	9.75	9.75	1 1/2	32	4	7000
AIS CO	REV 6-13 AIS COMPLIANT SWING FLEX [®] CHECK VALVE W/ BACKFLOW ACTUATOR AND MECHANICAL INDICATOR DATE 9-6-1																	
—	_																	
	VALVE AND MANUFACTURING CORP.													drwg. no. VM-503BFMIXD				

