SWING-FLEX®CHECK VALVE SERIES NO. 500XD ANSI CLASS 125 STANDARD MATERIALS OF CONSTRUCTION

PART NO.	PART NAME	MATERIAL
1	BODY	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
3	DISC	BUNA-N W/ ALLOY STEEL & NYLON REINFORCEMENT
4	COVER SEAL (14"-48") COVER SEAL (2"-12")	BUNA-N ASTM D2000 COMPRESSED NON-ASBESTOS FIBER
5A	COVER BOLT	ALLOY STEEL SAE J429 GRADE 5, PLATED
5C	WASHER	ALLOY STEEL, PLATED
6	BACKFLOW ACTUATOR (OPTIONAL, SIZES 2"-36")	ALUMINUM BRONZE, 17-4 STAINLESS STEEL
14	MECHANICAL INDICATOR (OPTIONAL, SIZES 3"-36")	ALUMINUM BRONZE, 17-4 STAINLESS STEEL

NOTE: ALL SPECIFICATIONS AS LAST REVISED.

DATE MATERIALS OF CONSTRUCTION DRWG. NO. VAL MATIC ®

6/12/19

VM-504XD-M

VALVE AND MANUFACTURING CORP.