

SWING-FLEX[®] CHECK VALVE

SERIES NO. 500XD ANSI CLASS 125

STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
3	DISC	BUNA-N W/ ALLOY STEEL & NYLON REINFORCEMENT
4	COVER SEAL (14"-36") COVER SEAL (2"-12")	BUNA-N ASTM D2000 COMPRESSED NON-ASBESTOS FIBER
5A	COVER BOLT	ALLOY STEEL SAE J429 GRADE 5, PLATED
5C	WASHER	ALLOY STEEL, PLATED
6	BACKFLOW ACTUATOR (OPTIONAL, SIZES 2"-36")	ALUMINUM BRONZE, 17-4 STAINLESS STEEL
6A	COVER PIPE PLUG	STEEL
6B	BODY PIPE PLUG (2"-6") BODY PIPE PLUG (8"-36")	STEEL STEEL, NICKEL PLATED
14	MECHANICAL INDICATOR (OPTIONAL, SIZES 3"-36")	ALUMINUM BRONZE, 17-4 STAINLESS STEEL

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

REV 11/8/19

MATERIALS OF CONSTRUCTION

DATE 6/12/19

VAL-MATIC[®]

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-504XD-M