

SWING-FLEX® CHECK VALVE W/OIL CUSHION

SERIES NO. 500AB ANSI CLASS 125

STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY	DUCTILE IRON ASTM A536, GRADE 65-45-12
2	COVER	DUCTILE IRON ASTM A536, GRADE 65-45-12
3	DISC	BUNA-N W/ ALLOY STEEL & NYLON REINFORCEMENT
4	COVER SEAL (4"-48") COVER SEAL (2"-3")	BUNA-N ASTM D2000 COMPRESSED NON-ASBESTOS FIBER
5A	COVER BOLT	ALLOY STEEL SAE J429 GRADE 5, PLATED
5B	COVER BOLT NUT (4"-12")	ALLOY STEEL SAE J429 GRADE 5, PLATED
5C	WASHER	ALLOY STEEL, PLATED
6A	COVER PIPE PLUG	STEEL
20	OIL CUSHION	ALUMINUM BRONZE, 17-4 STAINLESS STEEL

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

Revised 11-8-19

MATERIALS OF CONSTRUCTION

DATE 10/11/07

VAL-MATIC®

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-506AB-M