



SEE DRAWING NO. VM-9712B-M FOR ANSI CLASS 125 MATERIALS OF CONSTRUCTION.

**ANSI CLASS 250**

VALVE SIZE	MODEL NO.	A	B	C	D	E	F	G	BOLT SIZE	NO. OF BOLTS	H	J	K	L
12	9712B	24	17 <sup>3</sup> / <sub>4</sub>	20 <sup>1</sup> / <sub>2</sub>	2	12	26	11	1 <sup>1</sup> / <sub>8</sub>	16	7	20	11	5
14	9714B	30	20 <sup>1</sup> / <sub>4</sub>	23	2 <sup>1</sup> / <sub>8</sub>	14	29	12	1 <sup>1</sup> / <sub>8</sub>	20	4	21	8	5
16	9716B	30	22 <sup>1</sup> / <sub>2</sub>	25 <sup>1</sup> / <sub>2</sub>	2 <sup>1</sup> / <sub>4</sub>	16	32	14	1 <sup>1</sup> / <sub>4</sub>	20	5	23	9	5
18	9718B	33	24 <sup>3</sup> / <sub>4</sub>	28	2 <sup>3</sup> / <sub>8</sub>	18	36	15	1 <sup>1</sup> / <sub>4</sub>	24	3	24	7	5
20	9720B	32	27	30 <sup>1</sup> / <sub>2</sub>	2 <sup>1</sup> / <sub>2</sub>	20	39	16	1 <sup>1</sup> / <sub>4</sub>	24	3	25	8	6
24	9724B	38	32	36	2 <sup>3</sup> / <sub>4</sub>	24	46	19	1 <sup>1</sup> / <sub>2</sub>	24	1	27	4	6
30	9730B	52	39 <sup>1</sup> / <sub>4</sub>	43	3	30	55	23	1 <sup>3</sup> / <sub>4</sub>	28	1	35	6	8
36	9736B	59 <sup>1</sup> / <sub>2</sub>	46	50	3 <sup>3</sup> / <sub>8</sub>	36	65	27	2	32	5	39	2	8
42	9742B	62 <sup>1</sup> / <sub>2</sub>	52 <sup>3</sup> / <sub>4</sub>	57	3 <sup>11</sup> / <sub>16</sub>	42	73	32	2	36	5	43	5	8
48	9748B	65	60 <sup>3</sup> / <sub>4</sub>	65	4	48	82	37	2	40	2	52	8	8
54	9754B	78	*	*	*	54	90 <sup>7</sup> / <sub>8</sub>	39	*	*	7	55	5	8
60	9760B	87	*	*	*	60	99	42	*	*	7	64	5	8

NOTES:  
DIMENSIONS "K" AND "L" REPRESENT THE MINIMUM CLEARANCE REQUIRED TO REMOVE DASHPOT UNIT. HOWEVER DIMENSION "L" CAN REDUCED TO 1" IF SPACE REQUIREMENTS DICTATE.

\*FLANGE DIMENSIONS INDICATED BY ASTERIK TO BE SPECIFIED BY CUSTOMER

FOR VERTICAL FLOW UP INSTALLATION, CONSULT FACTORY.

Revised 9-23-20

**ANSI CLASS 250 TILTED DISC® CHECK VALVE WITH BOTTOM MOUNTED OIL DASHPOT**

DATE 8-12-80



VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-9712B