

SEE DRAWING NO. VM-15A-22-25-M FOR STANDARD MATERIALS OF CONSTRUCTION SEE DRAWING NO. VM-15A-22-25DISV-M FOR OPTIONAL "DISV" MATERIALS OF CONSTRUCTION

VALVE SIZE	STANDARD 15A MODEL NUMBER	INLET SIZE	OUTLET SIZE	MAX. WP. (PSI)	ORIFICE SIZE	VACUUM CHECK KIT
1/2"	15A*	½" NPT*	½" NPT	175	¹ / ₁₆ "	SPK-5VC
3/4"	15A.2	3⁄4" NPT	½" NPT	175	¹ / ₁₆ "	SPK-5VC
1"	15A.3	1" NPT	½" NPT	175	¹ / ₁₆ "	SPK-5VC

*THE VALVE BODY IS SUPPLIED WITH A 1" NPT CONNECTION. A REDUCER BUSHING IS SUPPLIED WHERE INDICATED

11 ORIFICE BUTTON BODY

COVER 12 PIVOT PIN

13 RETAINING RING (NOT SHOWN) LEVER FRAME

SEAT 14 PIPE PLUG

17 FLOAT RETAINER FLOAT

GASKET 21 LOCATOR

COVER BOLT 34 LOCK WASHERS

35 REDUCER BUSHING (WHEN SUPPLIED) 10 FLOAT ARM

REV 6-7-23

15A AIR RELEASE VALVE WITH VACUUM CHECK

DATE

4-18-11

DRWG. NO.

VMC-15AVC