



SEE DRAWING NO. VM-15A-22-25-M FOR STANDARD MATERIALS OF CONSTRUCTION
 SEE DRAWING NO. VM-15A-22-25DISV-M FOR OPTIONAL "DISV" MATERIALS OF CONSTRUCTION

VALVE SIZE	STANDARD MODEL NUMBER	INLET SIZE	OUTLET SIZE	MAX. WP. (PSI)	ORIFICE SIZE
1/2"	15A*	1/2" NPT*	1/2" NPT	175	1/16"
3/4"	15A.2	3/4" NPT	1/2" NPT	175	1/16"
1"	15A.3	1" NPT	1/2" NPT	175	1/16"

*THE VALVE BODY IS SUPPLIED WITH A 1" NPT CONNECTION. A REDUCER BUSHING IS SUPPLIED WHERE INDICATED

- | | |
|---------------|------------------------------------|
| 1 BODY | 11 ORIFICE BUTTON |
| 2 COVER | 12 PIVOT PIN |
| 3 LEVER FRAME | 13 RETAINING RING (NOT SHOWN) |
| 4 SEAT | 14 PIPE PLUG |
| 5 FLOAT | 17 FLOAT RETAINER |
| 6 GASKET | 21 LOCATOR |
| 7 COVER BOLT | 34 LOCK WASHERS |
| 10 FLOAT ARM | 35 REDUCER BUSHING (WHEN SUPPLIED) |

REV 6-7-23

15A AIR RELEASE VALVE

DATE 4-15-11

DRWG. NO.

VAL-MATIC

VALVE AND MANUFACTURING CORP.

VMC-15A